

Cards 🖳

Integrations

BIODIGITALPC® - M6

ADDC has developed a micro-form factor docking station for use within integrated products such as monitors, tablets, TVs, and micro client setups. Utilizing a small energy footprint, the M6 is the easiest way to integrate into larger platforms while maintaining standard connections.

The M6 docking station comes complete with a BioDigitalPC® docking connector, one USB 3.0 port, two USB 2.0 ports, one USB 2.0 4-pin header, one RJ-45 10/100 Mbps Ethernet connector, one PCIe x1 connector (optional), a 12VDC power connector, a Mini-DisplayPort video connector, and an external 12V PCIe power header.

BioDigitalPC® products encompass a revolutionary computing system which allows for maximum flexibility with minimum footprint, weight and energy consumption.





Tech Specs

SKU	ADDC-M6-I
Size	104mm x 45mm x 16mm
Specs	(1) USB 3.0 connector
	(2) USB 2.0 connectors
	(1) RJ45 10/100 Mbps Ethernet Connector
	PCIe x1 connector (optional)
	12VDC 2.5mm center pin input power jack
	Mini-DisplayPort (HDMI capable) connector
	Reset and system On/Off headers
	4A DC-DC Converter (for 3.3V req. in MiniDP & PCle x1)
	5V fan header
	Red 5V & 12V power LED indicator and header
	Green Card Detect LED indicator and header
	BioDigitalPC® 100-pin docking connector
	(3) 4mm mounting holes
	External 12V PCIe power header
	Headers are standard 0.1" pitch

🌐 www.addc.net

🔀 info@addc.net

🕓 516-673-4444

Microsoft Partner