

PodCom-D

The PodCom-D, a dual Card PodCom metal enclosure that passed the MIL-STD-810G test for shock and vibration. The PodCom-D chassis is IP67-rated and can withstand depths up to 1m (3.3 ft) for 30 minutes. The PodCom-D can operate on 12-32VDC and includes 2 USB 2.0 and 1 Mini-DisplayPort video output per slot on the chassis itself and 1 USB 2.0 and 1 Gigabit Ethernet port per slot available through a ruggedized MILSPEC connector. The PodCom-D can easily be stacked and secured to any other product in the PodCom product line. Heat sinks are removable. Proudly made in the USA. **TAA Compliant.**



Made in the USA

www.addc.com

info@addc.net

516-673-4444

10 Harbor Park Drive, Floor 2 Port Washington, NY 11050

Tech Specs

SKU	ADDC-PodCom-D
Size	7.37"L x 6" W x 2.5"H
Weight	3.6 lbs (4.2 lbs w/ cables)
Power	6-pin circular connector DC input cable 12-32 VDC Requires 60W when installing an operating system
System Includes	<p>Per Slot</p> <ul style="list-style-type: none"> - MiniDP - (2) USB 2.0 <p>Mil Spec Cable</p> <ul style="list-style-type: none"> - USB 2.0* - (1) Ethernet connection (10/100/1000) <p>* The PodCom-D can support USB 3.0 internally; however, the D38999 interface connectors do not support high speed data. The PodCom-S has mounting holes for size 9 D38999 high speed data connectors. Once it becomes available, this connector can be added to provide USB 3.0 functionality.</p>