

PodCom-R

The PodCom-R passed the MIL-STD-810G test for shock and vibration, protecting against dust and water intrusion. The PodCom-R chassis is IP67 rated and can withstand depths up to 1m (3.3 ft) for 30 minutes. The PodCom-R can operate on 12-32VDC and includes 1 USB 2.0 port, 1 USB 3.0 port and 1 Mini-DisplayPort video output on the chassis itself and 1 USB 2.0, 1 single PC Card router with 14 10/100 IP67 Ethernet ports, 2 general purpose RS-232 ports, and 1 RS-232 port for management of the integrated switch available through a ruggedized MIL-SPEC connector. The PodCom-R can easily be stacked and secured to any other product in the PodCom product line. Heat sinks are removable. Proudly made in the USA. **TAA Compliant.**



Tech Specs

SKU	ADDC-PodCom-R
Size	7"L x 6" W x 2.5"H
Weight	3.3 lbs (5.3 lbs w/ cables)
Power	6-pin circular connector DC input cable 12-32 VDC Requires 60W when installing an operating system
System Includes	<ul style="list-style-type: none"> - MiniDP - USB 2.0 - USB 3.0 Mil Spec Cable <ul style="list-style-type: none"> - USB 2.0 - (14) Ethernet connection (10/100) - (2) Serial DTE (RS-232) - (1) Serial DCE (RS-232)

Made in the USA

www.addc.com

info@addc.net

516-673-4444

10 Harbor Park Drive, Floor 2 Port Washington, NY 11050

intel. And **Microsoft** Partner