

PodCom-R

The PodCom-R metal enclosure holds one Card and was designed to meet MIL-STD 810 standards for shock and vibration. The PodCom-R chassis is IP67-rated and can withstand depths up to 1m (3.3 ft) for 30 minutes. The PodCom-R can operate on 12-32VDC and includes 1 USB 2.0 port, 1 USB 3.0 port and 1 Mini-DisplayPort video output on the chassis itself and 1 USB 2.0, 1 single PC Card router with 14 10/100 IP67 Ethernet ports, 2 general purpose RS-232 ports, and 1 RS-232 port for management of the integrated switch available through a ruggedized MIL-SPEC connector. The PodCom-R can easily be stacked and secured to any other product in the PodCom product line. Heat sinks are removable.



Tech Specs

SKU	ADDC-PodCom-R
Size	7"L x 6" W x 2.5"D
Weight	2.2 lbs (5.2 lbs w/ cables)
Power	5-pin Mil-5015 circular connector DC input cable 12-32 VDC
System Includes	<ul style="list-style-type: none"> - MiniDP - USB 2.0 - USB 3.0 Mil Spec Cable - USB 2.0* - (2) Serial DTE (RS-232) - (1) Serial DCE (RS-232) - (14) Ethernet Connections (10/100)